

**PTFE-COATED, InQwire® GUIDE WIRES**

catalog number	new configuration catalog number	description	size	length cm	core	heparin coated	# per box
STRAIGHT TIP WIRES							
<b>6676-A1</b>		Straight	.018" (0.46mm)	150	F		10
<b>6676-B3</b>		Straight	.018" (0.46mm)	180	F		5
<b>6676-C1</b>		Straight	.021" (0.53mm)	150	F		10
<b>6676-D3</b>		Straight	.021" (0.53mm)	180	F		5
	<b>IQ35F150S</b>	Straight	.035" (0.89mm)	150	F		10
	<b>IQH35F150S</b>	Straight	.035" (0.89mm)	150	F	H	10
	<b>IQ35F260S</b>	Straight	.035" (0.89mm)	260	F		10
<b>6690-41</b>		Straight	.035" (0.89mm)	150	M		10
6690-71		Straight	.035" (0.89mm)	150	M	H	10
<b>6690-61</b>		Straight	.038" (0.97mm)	150	M		10
	<b>IQ38F150S</b>	Straight	.038" (0.97mm)	150	F		10
	<b>IQ38F260S</b>	Straight	.038" (0.97mm)	260	F		10
<b>6646-11</b>		Straight 7cm TC	.035" (0.89mm)	145	M		10
	<b>IQ35F150NLT</b>	Newton; LT (13.5cm)	.035" (0.89mm)	150	F		10
	<b>IQH35F150NLT</b>	Newton; LT (13.5cm)	.035" (0.89mm)	150	F	H	10
	<b>IQ35F150LLT</b>	Newton; LLT (18.5cm)	.035" (0.89mm)	150	F		10
	<b>IQH35F150LLT</b>	Newton; LLT (18.5cm)	.035" (0.89mm)	150	F	H	10
	<b>IQ35F150LLLT</b>	Newton; LLLT(23.5cm)	.035" (0.89mm)	150	F		10
<b>6677-B1</b>		Newton; LLT (18.5cm) 3mm J	.035" (0.89mm)	150	F		10
	<b>IQ35F80B</b>	Bentson (23cm)	.035" (0.89mm)	80	F		10
	<b>IQ35F150B</b>	Bentson (23cm)	.035" (0.89mm)	150	F		10
<b>8819-D1</b>	<b>IQH35F150B</b>	Bentson (23cm)	.035" (0.89mm)	150	F	H	10
	<b>IQ35F180B</b>	Bentson (23cm)	.035" (0.89mm)	180	F		10
	<b>IQH35F180B</b>	Bentson (23cm)	.035" (0.89mm)	180	F	H	5
	<b>IQ35F260B</b>	Bentson (23cm)	.035" (0.89mm)	260	F		10
	<b>IQ38F150B</b>	Bentson (23cm)	.038" (0.97mm)	150	F		10
	<b>IQH38F150B</b>	Bentson (23cm)	.038" (0.97mm)	150	F	H	10
	<b>IQ35F150BST</b>	Bentson ST (10cm)	.035" (0.89mm)	150	F		10
	<b>IQ35F180BST</b>	Bentson ST (10cm)	.035" (0.89mm)	180	F		10
	<b>IQ38F150BST</b>	Bentson ST (10cm)	.038" (0.97mm)	150	F		10
<b>6680-61</b>		Super Stiff	.035" (0.89mm)	80	F		10
<b>6680-51</b>		Super Stiff	.035" (0.89mm)	100	F		10
<b>6680-11</b>		Super Stiff	.035" (0.89mm)	150	F		10
<b>6680-71</b>		Super Stiff	.035" (0.89mm)	180	F		5
<b>6680-23</b>		Super Stiff	.035" (0.89mm)	260	F		5
6680-31		Super Stiff	.038" (0.97mm)	150	F		10
6680-43		Super Stiff	.038" (0.97mm)	180	F		5
ROSEN-TIP WIRES							
	<b>IQ35F80J1O5RS</b>	1.5mm J (R)	.035" (0.89mm)	80	F		10
<b>6500-11</b>	<b>IQ35F150J1O5RS</b>	1.5mm J (R)	.035" (0.89mm)	150	F		10
<b>6609-13</b>	<b>IQ35F180J1O5RS*</b>	1.5mm J (R)	.035" (0.89mm)	180	F		5 /10*
<b>6609-33</b>		1.5mm J (R)	.035" (0.89mm)	260	F		5
	<b>IQ38F150J1O5RS</b>	1.5mm J (R)	.038" (0.97mm)	150	F		10
J-TIP WIRES							
	<b>IQ35F150J1O5</b>	1.5mm J	.035" (0.89mm)	150	F		10
	<b>IQH35F150J1O5</b>	1.5mm J	.035" (0.89mm)	150	F	H	10
<b>6693-A1</b>		1.5mm J	.035" (0.89mm)	150	M		10

All "J" tip fixed core wires are finger-straightenable. FB = Firm Body ST = Short Taper  
H= Heparin Coating (R) = Rosen F=Fixed Core M= Moveable Core TC = Tapered Core  
\* New guide wire configurations packaged 10 per box. Original guide wires packaged 5 per box.

**PTFE-COATED, InQwire® GUIDE WIRES** (continued)

catalog number	new configuration catalog number	description	size	length cm	core	heparin coated	# per box
J-TIP (continued)*							
6682-H1		3mm J	.014" (0.36mm)	150	F		10
<b>6682-J3</b>		3mm J	.014" (0.36mm)	180	F		5
<b>6682-K1</b>		3mm J	.018" (0.46mm)	150	F		10
<b>6682-L3</b>		3mm J	.018" (0.46mm)	180	F		5
<b>6682-M1</b>		3mm J	.021" (0.53mm)	150	F		10
<b>6682-N3</b>		3mm J	.021" (0.53mm)	180	F		5
<b>6682-E1</b>		3mm J	.025" (0.64mm)	150	F		10
	<b>IQ35F80J3</b>	3mm J	.035" (0.89mm)	80	F		10
<b>6682-41</b>	<b>IQ35F150J3</b>	3mm J	.035" (0.89mm)	150	F		10
<b>6682-C1</b>	<b>IQH35F150J3</b>	3mm J	.035" (0.89mm)	150	F	H	10
<b>6682-P1</b>	<b>IQ35F180J3*</b>	3mm J	.035" (0.89mm)	180	F		5 /10*
	<b>IQ35F260J3</b>	3mm J	.035" (0.89mm)	260	F		10
<b>6693-41</b>		3mm J	.035" (0.89mm)	150	M		10
<b>6693-71</b>		3mm J	.035" (0.89mm)	150	M	H	10
<b>6684-41</b>		3mm J TC	.035" (0.89mm)	150	M		10
<b>6647-11</b>		3mm J 7cm TC	.035" (0.89mm)	145	M		10
	<b>IQ38F150J3</b>	3mm J	.038" (0.97mm)	150	F		10
<b>6682-D1</b>	<b>IQH38F150J3</b>	3mm J	.038" (0.97mm)	150	F	H	10
	<b>IQ38F260J3</b>	3mm J	.038" (0.97mm)	260	F		10
<b>6693-61</b>		3mm J	.038" (0.97mm)	150	M		10
<b>6693-81</b>		3mm J	.038" (0.97mm)	150	M	H	10
6684-61		3mm J TC	.038" (0.97mm)	150	M		10
	<b>IQ35F150J3F</b>	3mm J FB	.035" (0.89mm)	150	F		10
	<b>IQH35F150J3F</b>	3mm J FB	.035" (0.89mm)	150	F	H	10
	<b>IQ35F180J3F</b>	3mm J FB	.035" (0.89mm)	180	F		10
	<b>IQH35F180J3F</b>	3mm J FB	.035" (0.89mm)	180	F	H	5
	<b>IQ38F150J3F</b>	3mm J FB	.038" (0.97mm)	150	F		10
	<b>IQH38F150J3F</b>	3mm J FB	.038" (0.97mm)	150	F	H	10
	<b>IQ38F180J3F</b>	3mm J FB	.038" (0.97mm)	180	F		10
	<b>IQ35F150J6</b>	6mm J	.035" (0.89mm)	150	F		10
	<b>IQH35F70J6</b>	6mm J	.035" (0.89mm)	70	F	H	10
<b>6694-21</b>		6mm J	.035" (0.89mm)	150	M		10
	<b>IQ38F150J6</b>	6mm J	.038" (0.97mm)	150	F		10
	<b>IQH38F70J6</b>	6mm J	.038" (0.97mm)	70	F	H	10
	<b>IQ35F150J15</b>	15mm J	.035" (0.89mm)	150	F		10
	<b>IQH35F150J15</b>	15mm J	.035" (0.89mm)	150	F	H	10
	<b>IQ38F150J15</b>	15mm J	.038" (0.97mm)	150	F		10
<b>8820-B1</b>		15mm J	.035" (0.89mm)	150	M		10
FIXED CORE, DOUBLE-ENDED							
	<b>IQ35F150J10S</b>	1.5mm J/Straight	.035" (0.89mm)	150	F		10
	<b>IQ35F150J3S</b>	3mm J/Straight	.035" (0.89mm)	150	F		10
	<b>IQH35F150J3S</b>	3mm J/Straight	.035" (0.89mm)	150	F	H	10
	<b>IQ35F150J3SHD</b>	3mm J/Straight /Heavy Duty	.035" (0.89mm)	150	F		10

All "J" tip fixed core wires are finger-straightenable. FB = Firm Body ST = Short Taper  
H= Heparin Coating (R) = Rosen F=Fixed Core M= Moveable Core TC = Tapered Core

\* New guide wire configurations packaged 10 per box. Original guide wires packaged 5 per box

DIAGNOSTIC GUIDE WIRES